$0.9 \cdot 1$ 

## **SAFETY DATA SHEET**

Page 1 of 7 **SDS-067G** 

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 2001/58 & 1272/2008/EC Standards

SDS Revision: 4.1

SDS Revision Date: 2/8/2016

	1. PRODUCT & COMPANY IDENTIFICATION							
1.1	Product Name:	OPI NAIL ENVY NATURAL NAIL STRENGTHENER ORIGINAL FORMULA						
1.2	Chemical Name:	Solvent Mixture						
1.3	Synonyms:	NA NA						
1.4	Trade Names:	NTT80, NTT84						
1.5	Product Use:	Cosmetic Use Only						
1.6	Distributor's Name:	OPI Products, Inc.						
1.7	Distributor's Address:	13034 Saticoy Street, No. Hollywood, CA 91605 USA						
1.8	Emergency Phone:	CHEMTREC: +1 (703) 527-3887 / +1 (800) 424-9300 (CCN 16377)						
1.9	Business Phone / Fax:	+1 (818) 759-2400 / +1 (818) 759-5776						

#### 2. HAZARDS IDENTIFICATION

2.1 Hazard Identification:

This product is classified as a hazardous substance and as dangerous goods according to the classification criteria of NOHSC: 1008 (2004) and ADG Code (Australia).

DANGER! HIGHLY FLAMMABLE LIQUID AND VAPOR. MAY CAUSE AN ALLERGIC SKIN REACTION. CAUSES SERIOUS EYE IRRITATION. MAY CAUSE RESPIRATORY IRRITATION.

<u>Classification</u>: Flam. Liq. 2; Skin Sens. 1A; Eye Irrit. 2B: STOT SE 3

<u>Hazard Statements</u> (H): H225 – Highly flammable liquid and vapor. H315 – Causes skin irritation.

H317 – May cause an allergic skin reaction. H319 – Causes serious eye irritation. H335 – May cause respiratory irritation. H336 – May cause drowsiness or dizziness.

Precautionary Statements (P): P210 – Keep away from heat/sparks/open flame/hot surfaces – No Smoking. P233 – Keep container tightly closed. P243 – Take precautionary measures against static discharge. P261 – Avoid breathing fume/mist/vapors/spray. P264 – Wash exposed skin areas thoroughly with soap and water after handling. P272 – Contaminated work clothing should not be allowed out of the workplace. P280 – Wear protective gloves/eye protection/face protection. P281 – Use personal protective equipment as required. P301+P310 IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician. P302+P352 – IF ON SKIN: Wash with soap and water. P305+P351+P338 – IF IN EYES: Rinse continuously with water for several minutes. Remove contact lenses if present and easy to do – continue rinsing. P333+P313 – If skin irritation or a rash occurs – Get medical advice/attention. P321 – For specific first aid treatment (See Section 4 of this Safety Data Sheet). P363 – Wash contaminated clothing before reuse. P370+P378 – In case of fire, CO<sub>2</sub>, Halon (if permitted), dry chemical, or foam for extinction. P403+P235 – Store in a well-ventilated place. Keep cool. P501 – Dispose of contents/container to a licensed treatment, storage or disposal facility (TSDF).



### 3. COMPOSITION & INGREDIENT INFORMATION

					EXPOSURE LIMITS IN AIR (mg/m³)								
					ACGIH ppm		NOHSC			OSHA ppm			
							ppm						
CHEMICAL NAME(S)	CAS No.	RTECS No.	EINECS No.	%	TLV	STEL	ES- TWA	ES- STEL	ES- PEAK	PEL	STEL	IDLH	OTHER
ETHYL ACETATE	141-78-6	AH5425000	201-550-6	10-30	400	400	200	400	NF	NA	NA	2000	400 TWA
EINTLACETATE	Flam. Liq. 2; E	ye Irrit. 2; STOT	SE 3; H225, H31	9, H336									
BUTYL ACETATE	123-86-4	AF7350000	204-658-1	10-30	150	200	150	200	NF	200	200	1700	100 NIOSH
BOTTLACLIATE	Flam. Liq. 3; S	TOT SE 3; H226,	H336										
NITROCELLULOSE	9004-70-0	AH5425000	NA	10-30	400	400	400	200	NF	NA	NA	2000	
NITROCLEUCOSE	Flam. Liq. 2; H	225											
PROPYL ACETATE	109-60-4	AJ3675000	203-686-1	10-30	200	250	835	1040	NF	200	840	1700	
FROF IL ACLIATE	Flam. Liq. 2, E	ye Irrit. 2, STOT	SE 3; H225, H31	9, H336									
TOSYLAMIDE/FORMALDEHYDE RESIN	25035-71-6	QW0970000	NA	5.0-10	(10)	NE	NF	NF	NF	(10)	NE	NE	
10000000// 41 001101	67-63-0	TR4955000	NA	5.0-10	NE	NE	NF	NF	NF	NE	NE	NE	
SOPROPYL ALCOHOL	Flam. Liq. 2; S	kin Irrit. 3; Eye Irr	it. 2A; STOT SE	3; H225, F	316, H	319							•
TRIPHENYL PHOSPHATE	115-86-6	TC840000	204-112-2	1.0-5.0	NA	NA	NF	NF	NF	NA	NA	NA	
TRIPHENTL PHOSPHATE	Aquatic Acute	1; Aquatic Chroni	ic 1; H400, H410										
TRIMETHYL PENTANYL DIISOBUTYRATE	6846-50-0	SA142000	229-937-9	1.0-5.0	NA	NA	NF	NF	NF	NA	NA	NA	
N BUTYL ALCOHOL	71-36-3	EO1400000	200-751-6	1.0-5.0	NA	NA	NF	NF	50	100	NA	1400	
N-BUTYL ALCOHOL	Flam. Liq. 3; A	cute Tox. 4; Skin	Irrit. 2; Eye Dam	. 1; STOT	SE 3; F	1226, H	302, H3	315, H3	18, H33	35, H33	6		
METHYLENE GLYCOL	463-57-0	TY200000	207-339-5	1.0-5.0	NA	0.3	1.2	2	2.5	5	2	20	FORMALDEHYDE
METHYLENE GLYCOL	Carc. 2; H351,	H317											
STEARALKONIUM BENTONITE	71011-24-0	NA	NA	1.0-5.0	NA	NA	NF	NF	NF	NA	NA	15	DUST
HYDROLYZED WHOLE WHEAT PROTEIN	70084-87-6	NA	NA	0.1-1.0	NA	NA	NF	NF	NF	NA	NA	NA	
CAMPHOR	76-22-2	EX1225000		0.1-1.0	2	NA	12	19	NF	4	NA	200	
	Fiam. Soi. 2, A	cute Tox. 4, STO	1 SE 2; HZZ8, H	აა∠, H3/1									

# $\mathbf{J} \cdot \mathbf{P} \cdot \mathbf{I}$

4.3

4.4

4.5

4.6

4.7

Symptoms of Overexposure:

Acute Health Effects:

Chronic Health Effects:

Medical Conditions

Aggravated by Exposure:

Target Organs:

## **SAFETY DATA SHEET**

Page 2 of 7

2

3

0

В

SDS-067G Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 2001/58 & 1272/2008/EC Standards SDS Revision: 4.1 SDS Revision Date: 2/8/2016 3. COMPOSITION & INGREDIENT INFORMATION -cont'd. EXPOSURE LIMITS IN AIR (mg/m<sup>3</sup>) ACGIH NOHSC OSHA ppm ppm ppm ES-ES-ES-CHEMICAL NAME(S) CAS No. RTECS No. EINECS No. STEL STEL PEAK PEL STEL IDLH OTHER SA9100000 NA 0.1-1.0 50 NF 20 240 1800 123-42-2 240 238 NF DIACETONE ALCOHOL Eye Irrit, 2: H319 214-073-3 0.1-1.0 NA NA NF NF NF NA NA NA 1077-56-1 NA ETHYL TOSYLAMIDE 131-56-6 DJ0700000 205-029-4 0.1-1.0 NA NA NF NF NF NA NA NA BENZOPHENONE-1 Sin Irrit. 2; Eye Irrit. 2; STOT SE 3; H315, H319, H335 77-92-9 GE7350000 201-069-1 0.1-1.0 NA NA NF NF NF NA NA NA CITRIC ACID NA NA NA NA NF NF NA NA NA 9006-65-9 0.1-1.0 NF DIMETHICONE RU4375000 137-08-6 205-278-9 0.1-1.0 NA NA NF NF NF NA NA NA CALCIUM PANTOTHENATE 8148-1 OZ4725000 212-782-2 0.1-1.0 NA NA NF NF NF NA NA NA CI 60725 (VIOLET 2) 13463-67-7 XR2275000 236-675-5 0.1-1.0 NA NA NF NF NF NA NA NA CI 77891 (TITANIUM DIOXIDE) 4. FIRST AID MEASURES First Aid: 4.1 If ingested, do not induce vomiting. If product has been swallowed, drink plenty of water or milk Ingestion: IMMEDIATELY. If the patient is vomiting, continue to offer water or milk. Never give water or milk to an unconscious person. Contact the nearest Poison Control Center or local emergency number. Provide an estimate of the time at which the material was ingested and the amount of the substance that was Splashes are not likely; however, if product gets in the eyes, flush with copious amounts of lukewarm Eyes: water for at least 15 minutes. If irritation occurs, contact a physician. If irritation occurs and product is on the skin, rinse thoroughly with lukewarm water, followed by a thorough Skin: washing of the affected area with soap and water. If irritation, redness or swelling persists, contact a physician immediately. Inhalation: Remove victim to fresh air at once. 4.2 Effects of Exposure: If product is swallowed, may cause nausea, vomiting and/or diarrhea and central nervous system Ingestion: depression. Irritating to the eyes. Symptoms of overexposure may include redness, itching, irritation and watering. Eyes: Skin: May be irritating to skin in some sensitive individuals, especially after prolonged and/or repeated contact. Vapors of this product may be slightly irritating to the nose, throat and other tissues of the respiratory Inhalation: system. Symptoms of overexposure can include coughing, wheezing, nasal congestion, and difficulty breathing. Inhalation of vapors exceeding the levels listed in Section 3 (Composition and Ingredient Information) can cause central nervous system depression (e.g., drowsiness, dizziness, headaches,

Overexposure in eyes may cause redness, itching and watering.

Pre-existing dermatitis, other skin conditions, and disorders of the

drowsiness, dizziness, headaches and nausea.

target organs (eyes, skin, and respiratory system).

Eyes, Skin, Respiratory System.

None known.

Symptoms of skin overexposure in individuals may include redness, itching, and irritation of affected areas.

Mild to moderate irritation to eyes and skin near affected areas. Additionally, high concentrations of vapors can cause

**HEALTH** 

**EYES** 

**FLAMMABILITY** 

**PHYSICAL HAZARDS** 

PROTECTIVE EQUIPMENT

SKIN

8.3

8.4

Respiratory Protection:

Eve Protection:

Page 3 of 7

SAFETY DATA SHEET SDS-067G Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 2001/58 & 1272/2008/EC Standards SDS Revision: 4.1 SDS Revision Date: 2/8/2016 5. FIREFIGHTING MEASURES DANGER! HIGHLY FLAMMABLE LIQUID AND VAPOR! Keep away from heat, lit cigarettes, 5.1 Fire & Explosion Hazards: sparks & open flame. Keep container closed. 5.2 Extinguishing Methods: CO2, Halon (if permitted), Dry Chemical, Foam, as authorized. Firefighting Procedures: 5.3 This product is a Class IB flammable liquid. When involved in a fire, this product will ignite readily and decompose to produce carbon oxides. Vapors of this product are heavier than air and may travel to a source of ignition and flash back to a leaking or open container. First responders should wear eye protection. Structural firefighters must wear SCBAs and full protective equipment. Use a water spray or fog to reduce or direct vapors. Water may not be effective in actually extinguishing a fire involving this product. HazChem Code: 3(Y)E Hazard Identification Number: 33 6. ACCIDENTAL RELEASE MEASURES Spills 6.1 Before cleaning any spill or leak, individuals involved in spill cleanup must wear appropriate Personal Protective Equipment. For small spills (e.g., < 1 gallon (3.8 L)) wear appropriate personal protective equipment (e.g., goggles, gloves). Maximize ventilation (open doors and windows) and secure all sources of ignition. Remove spilled material with absorbent material and place into appropriate closed container(s) for disposal. Dispose of properly in accordance with local, state and federal regulations. Wash all affected areas and outside of container with plenty of warm water and soap. Remove any contaminated clothing and wash thoroughly before reuse. For large spills (e.g., ≥ 1 gallon (3.8 L)), deny entry to all unprotected individuals. Dike and contain spill with inert material (e.g., sand or earth). Use ONLY non-sparking tools for recovery and cleanup. Transfer liquid to containers for recovery or disposal and solid diking material to separate containers for proper disposal. Remove contaminated clothing promptly and wash affected skin areas with soap and water. Keep spills and cleaning runoffs out of municipal sewers and open bodies of water. 7. HANDLING & STORAGE INFORMATION Avoid prolonged contact with the product. Avoid breathing vapors of this product. Use in a well-ventilated location (e.g., 7.1 Work & Hygiene Practices: local exhaust ventilation, fans). After use, wash hands and exposed skin with soap and water. Do not eat, drink or smoke while handling product. 7.2 Storage & Handling: Keep this material away from heat, sparks and open flame. Open containers slowly on a stable surface. container closed tightly when not in use. Empty container may contain residual amounts of this product; therefore, empty containers should be handled with care. Store containers in a cool, dry location, away from direct sunlight, other light sources, or sources of intense heat. Store away from incompatible materials (See Section 10). Special Precautions: 7.3 Open containers slowly on a stable surface. Keep container tightly closed when not in use. Empty containers may contain residual amounts of this product; therefore, empty containers should be handled with care. **EXPOSURE CONTROLS & PERSONAL PROTECTION ACGIH** NOHSC OSHA OTHER Exposure Limits: FS. ppm (mg/m<sup>3</sup>) FS. CHEMICAL NAME(S) TLV STEL TWA STE PEL STEL IDLH PEAK ETHYL ACETATE 400 400 200 NA 2000 400 TWA 400 NF NA **BUTYL ACETATE** 150 150 NF 1700 100 NIOSH 200 200 200 200 400 NA NITROCELLULOSE 400 400 200 NF PROPYL ACETATE 200 250 835 1040 NF 200 840 1700 TOSYLAMIDE/FORMALDEHYDE (10)NA NF NF NF NA (10)NA RESIN N-BUTYL ALCOHOL NA NΑ NF NF 50 NA 1400 100 METHYLENE GLYCOL NA FORMALDEHYDE 0.3 1.2 2 2.5 5 2 20 STEARALKONIUM BENTONITE NA NA NF NF NF NA NA 15 DUST CAMPHOR NA NF NA 200 12 19 4 DIACETONE ALCOHOL 50 240 238 NF NF 20 240 1800 ETHANOL (SD ALCOHOL 40B) 1000 1900 1880 NF NF 1000 1900 3300 Ventilation & Engineering No special respiratory protection is required under typical circumstances of use or handling. In instances where vapors 8.2 Controls: or sprays of this product are generated, and respiratory protection is needed, use only protection authorized by 29 CFR

§1910.134, applicable U.S. State regulations, or the Canadian CAS Standard Z94.4-93 and applicable standards of

Wear protective eyewear (e.g., safety glasses with side-shield) at all times when handling this product. Always use protective evewear when cleaning spills or leaks. Contact lenses pose a

AVOID SKIN CONTACT DUE TO SENSITIZING POTENTIAL. If anticipated that prolonged &

repeated skin contact will occur during use of this product, wear latex or rubber gloves for routine industrial use. If necessary, refer to U.S. OSHA 29 CFR §1910.138, the appropriate standards of

Canadian Provinces, EC member States, or Australia.

Canada, of the E.C. member states.

special hazard; soft lenses may absorb and concentrate irritants.



# $O \cdot P \cdot I$

### SAFETY DATA SHEET

Page 4 of 7 SDS-067G

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 2001/58 & 1272/2008/EC Standards SDS Revision Date: 2/8/2016 8. EXPOSURE CONTROLS & PERSONAL PROTECTION - cont'd Hand Protection: AVOID SKIN CONTACT DUE TO SENSITIZING POTENTIAL. However, no special body 8.5 protection is required under typical circumstances of use and handling. If necessary, refer to appropriate standards of Canada, the E.C. member states, or U.S. OSHA. 8.6 Body Protection: No special respiratory protection is required under typical circumstances of use or handling. In instances where vapors or sprays of this product are generated, and respiratory protection is needed, use only protection authorized by 29 CFR §1910.134, applicable U.S. State regulations, or the Canadian CAS Standard Z94.4-93 and applicable standards of Canadian Provinces, EC member States, or Australia. 9. PHYSICAL & CHEMICAL PROPERTIES Appearance: Viscous liquid, various colors 9.2 Odor Odor Threshold: 9.3 NA 9.4 pH: NA 9.5 Melting Point/Freezing Point: NA 9.6 Initial Boiling Point/Boiling 171 - 640 °F Range: 9.7 Flashpoint 77.2-337.8 °C (171-640 °F) 9.8 Upper/Lower Flammability -4 °C (24 °F) estimated 9.9 Vapor Pressure: NA 9.10 Vapor Density: NA Relative Density: 0.9998 - 1.0008 9.11 Solubility: Insoluble 9.12 9.13 Partition Coefficient (log Pow): NA 9.14 **Autoignition Temperature** NA 9.15 Decomposition Temperature: NA 9.16 1000-3000 cPs 9.17 Other Information: NA 10. STABILITY & REACTIVITY 10.1 Stability: Stable under ambient conditions when stored properly (See Section 7, Storage and Handling). 10.2 Hazardous Decomposition If exposed to extremely high temperatures, the products of thermal decomposition may include irritating vapors and Products: carbon oxide gases (e.g., CO, CO<sub>2</sub>). 10.3 Hazardous Polymerization: May occur, if exposed to extremely high temperatures. 10.4 Conditions to Avoid: High temperatures, direct sunlight, sources of heat and incompatible materials. 10.5 Incompatible Substances This product is incompatible with strong oxidizers, (e.g., peroxides, superoxides), strong acids (e.g., hydrochloric or muriatic acids), nitrates, or strong bases (e.g., lye, potassium hydroxide). 11. TOXICOLOGICAL INFORMATION Absorption: YES Routes of Entry Inhalation: YES Ingestion: YES 11.1 Toxicity Data: This product has NOT been tested on animals to obtain toxicology data. Toxicology data, found in scientific literature, is available for some of the components of the product and is presented below: Ethyl Acetate: LD<sub>50</sub> (oral, rat) = 5,620 mg/kg; LD<sub>50</sub> (oral, mouse) = 4,100 mg/kg; LC<sub>50</sub> (inh-6h, rat) = 16,000 ppm; Methylene Glycol:  $LD_{50}$  (oral, rat) = 5,682 mg/kg;  $LD_{50}$  (oral, mouse) = 7,300 mg/kg;  $LC_{50}$  (inh-6h, rat) = 64,000 ppm/4h 11.3 Acute Toxicity: See Section 4.4 Chronic Toxicity: 11.4 See Section 4.5 This product contains Methylene Glycol (as Formaldehyde) which is listed ACGIH A2 - Suspected Human Carcinogen; 11.5 Suspected Carcinogen: NIOSH - occupational carcinogen; NTP - Suspected carcinogen; OSHA - Possible select carcinogen; California -Carcinogen initial date 01/01/1988. This product contains Ethyl Acetate and Isopropyl Alcohol, which are not carcinogenic to humans, but are listed as Group 3 carcinogens by the IARC. Reproductive Toxicity: 11.6 This product is not reported to cause reproductive toxicity in humans. Mutagenicity: This product is not reported to produce mutagenic effects in humans. Embryotoxicity: This product is not reported to produce embryotoxic effects in humans. Teratogenicity: This product is not reported to cause teratogenic effects in humans. Reproductive Toxicity: This product is not reported to cause reproductive effects in humans Irritancy of Product: 117 See Section 4.3 11.8 Biological Exposure Indices: 11.9 Physician Recommendations: Treat symptomatically.

 $0.9 \cdot 1$ 

## SAFETY DATA SHEET

Page 5 of 7 **SDS-067G** 

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 2001/58 & 1272/2008/EC Standards SDS Revision: 4.1 SDS Revision Date: 2/8/2016 12. ECOLOGICAL INFORMATION 12 1 Environmental Stability: The components of this product will slowly degrade over time into a variety of organic compounds. environmental data available for the components of this product are as follows: Ethyl Acetate: Koc = 0.73. Water solubility: 64,000 mg/l. Bioconcentration Factor = 4-14. Bioconcentration is not anticipated to be significant. This compound can be removed from contaminated environments from volatilization, and biodegradation. This compound's half-life in water is 6.1 hours. Butyl Acetate: Koc = 1.82. Water solubility: 120 parts H<sub>2</sub>O at 25°C (77°F). Bioconcentration Factor = 4-14. Bioconcentration is not anticipated to be significant. This compound can be removed from contaminated environments from volatilization, and biodegradation. This compound's half-life in water is 6.1 hours. <u>Isopropyl Alcohol</u>: Log K<sub>OW</sub> = 0.05-0.14. Isopropyl alcohol occurs naturally; it is generated during microbial degradation of plant and animal wastes. When released on land or water, it is apt to volatilize and biodegrade. The estimated halflife in water is 5.4 days. Isopropyl alcohol is not expected to bioconcentrate. 12.2 Effects on Plants & Animals: There are no specific data available for this product. 12.3 Effects on Aquatic Life: There are no specific data available for this product; however, very large releases of this product may be harmful or fatal to overexposed aquatic life. 13. DISPOSAL CONSIDERATIONS Waste Disposal: 13.1 Waste disposal must be in accordance with appropriate Federal, state, and local regulations. 13.2 Special Considerations: U.S. EPA Waste Number: D001 (characteristic - ignitable) 14. TRANSPORTATION INFORMATION The basic description (ID Number, proper shipping name, hazard class & division, packing group) is shown for each mode of transportation. Additional descriptive information may be required by 49 CFR, IATA/ICAO, IMDG and the CTDGR. 49 CFR (GND): UN1263, PAINT, 3, II, LTD QTY (IP VOL ≤ 1.0 L) or CONSUMER COMMODITY, ORM-D - until 01/01/2021 IATA (AIR): 14.2 ID8000, CONSUMER COMMODITY, 9 (IP VOL ≤ 0.5 L) UN1263, PAINT, 3, II (IP VOL ≤ 1.0 L) IMDG (OCN): 14.3 UN1263, PAINT, 3, II, LTD QTY (IP VOL ≤ 1.0 L) 14.4 TDGR (Canadian GND): UN1263, PAINT, 3, II, LTD QTY (IP VOL ≤ 1.0 L); or "LIMITED QUANTITY" or "QUANTITÉ LIMITÉE" or "LTD QTY" or "QUANT LTÉE" (≤ 1.0 L) 14.5 ADR/RID (EU): UN1263, PAINT, 3, II, LTD QTY (IP VOL ≤ 1.0 L) SCT (MEXICO): UN1263, PINTURA, 3, II, CANTIDAD LIMITADA (IP VOL ≤ 1.0 L) 14.7 ADGR (AUS): UN1263, PAINT, 3, II, LTD QTY (IP VOL ≤ 1.0 L) \* This product may also be shipped as an Excepted Quantity (Inner Package Volume ≤ 30 mL, Total Quantity ≤ 500 mL per Outer Package) 15. REGULATORY INFORMATION SARA Reporting 15.1 This product contains Isopropanol, Methylene Glycol (as Formaldehyde) and Dibutyl Phthalate, substances subject to Requirements: SARA Title III, See Section 313 reporting requirements. This product contains Ethyl Acetate, a substance that is subject to SARA Title III, section 304 reporting. 15.2 SARA Threshold Planning There are no specific Threshold Planning Quantities for the components of this product. Quantity: 15.3 TSCA Inventory Status: The components of this product are listed on the TSCA Inventory. CERCLA Reportable Quantity 15.4 Ethyl Acetate: 2,270 kg (5,000 lbs); Butyl Acetate: 2,270 kg (5,000 lbs); Formaldehyde: 45.4 kg (100 lbs). (RQ): 15.5 Other Federal Requirements: This product complies with the appropriate sections of the Food and Drug Administration's 21 CFR subchapter G (Cosmetics). Methylene Glycol (as Formaldehyde) is listed as a Hazardous Air Pollutant (HAP). This material does not contain any Class 1 Ozone depletors. This material does not contain any Class 2 Ozone depletors. Methylene Glycol (as Formaldehyde) is listed as a Hazardous Substance under the CWA. Methylene Glycol (as Formaldehyde) is considered highly hazardous by OSHA. 15.6 Other Canadian Regulations: This product has been classified according to the hazard criteria of the CPR and the Safety Data Sheet contains all of the information required by the CPR. The components of this product are listed on the DSL/NDSL. None of the components of this product are listed on the Priorities Substances List. WHMIS B2, D2B (Flammable Liquid, Other Toxic Effects)

 $O \cdot P \cdot I$ 

# **SAFETY DATA SHEET**

Page 6 of 7 **SDS-067G** 

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 2001/58 & 1272/2008/EC Standards

SDS Revision: 4.1

SDS Revision Date: 2/8/2016

		15. REGULATORY INFO					
15.7	State Regulatory Information:	Butyl Acetate is found on the following state criteria lists: California OSHA Hazardous Substances List (CA), Delaware Air Quality Management List (DE), Massachusetts Hazardous Substances List (MA), New Jersey Right-to-Know List (NJ), New York List of Hazardous Substances (NY), Pennsylvania Right-to-Know List (PA), Washington Permissible Exposures List for Air Contaminants (WA), and Wisconsin Hazardous Substances List (WI).  Ethyl Acetate is found on the following state criteria lists: CA, DE, MA, MN, NJ, NY, PA, and WA.  Isopropanol is found on the following state criteria lists: CA, MA, MN, NJ, PA, and WA.  Nitrocellulose is found on the following state criteria lists: FL, MA, and PA.  Formaldehyde is found on the following state criteria list: CA, FL, NJ, PA, MA, and MN.					
		No other ingredients in this product, present in a concentration of 1.0% or greater, are listed on any of the following state criteria lists: Delaware Air Quality Management List (DE), Florida Toxic Substances List (FL), Massachusetts Hazardous Substances List (MA), Michigan Critical Substances List (MI), Minnesota Hazardous Substances List (MN), New Jersey Right-to-Know List (NJ), New York Hazardous Substances List (NY), Pennsylvania Right-to-Know List (PA), Washington Permissible Exposures List (WA), Wisconsin Hazardous Substances List (WI).  WARNING: This product contains Methylene Glycol (as Formaldehyde), a chemical know to the state of California to cause cancer. California No Significant Risk Level NOEL = 40 µg/day.					
15.8	Other Requirements:	The primary components of this product are listed					
			- Highly flammable. <u>Safety Phrases</u> (S): 2-7-16 - ghtly closed. Keep away from sources of ignition –				
		Ethyl Acetate: Flammable (F). Risk Phrases (R): 11-36/37/38 – Highly flammable. Irritating to eyes, respiratory system and skin. Safety Phrases (S): 2-16-23-29-33 – Keep out of the reach of children. Keep away from sources of ignition - No smoking. Do not breathe gas, fumes, vapor or spray. Do not empty into drains. Take precautionary measures against static discharges.  Butyl Acetate: Flammable (F). Risk Phrases (R): Flammable. Safety Phrases (S): 9-16-33 - Keep container in a well-ventilated place. Keep away from sources of ignition - No smoking. Take precautionary measures against static discharges.					
		Isopropanol: Flammable (F). Risk Phrases (R): 11-36/37 – Highly flammable. Irritating to eyes and respiratory system. Safety Phrases (S): 2-7-16-24/25/26 – Keep out of the reach of children. Keep container tightly closed. Avoid contact with skin and eyes. In case of contact with eyes, rinse					
	immediately with plenty of water and seek medical advice.						
		16 OTHER INFO	DRMATION				
16.1	16.1 Other Information:  DANGER! HIGHLY FLAMMABLE LIQUID AND VAPOR. MAY CAUSE AN ALLERGIC SKIN REACTION. CAUSES SERIOUS EYE IRRITATION. MAY CAUSE RESPIRATORY IRRITATION. MAY CAUSE DROWSINESS OR DIZZINESS. Keep away from heat/sparks/open flame/hot surfaces – No Smoking. Keep container tightly closed. Take precautionary measures against static discharge. Avoid breathing fume/mist/vapors/spray. Wash exposed skin areas thoroughly with soap and water after handling. Avoid eye contact. Wear protective gloves/eye protection/face protection. IF ON SKIN: Wash with soap and water. IF IN EYES: Rinse continuously with water for several minutes. Remove contact lenses if present and easy to do – continue rinsing. If skin irritation or a rash occurs – Get medical advice/attention. Store in a well-ventilated place. Keep cool. Use only as directed. KEEP OUT OF REACH OF CHILDREN. WARNING: This product contains Methylene Glycol (as Formaldehyde), a chemical known to the state of						
16.2	Terms & Definitions:	See last page of this Safety Data Sheet.					
16.3	Disclaimer:	This Safety Data Sheet is offered pursuant to OSHA's Hazard Communication Standard, 29 CFR §1910.1200. Other government regulations must be reviewed for applicability to this product. To the best of ShipMate's & OPI's knowledge, the information contained herein is reliable and accurate as of this date; however, accuracy, suitability or completeness is not guaranteed and no warranties of any type, either expressed or implied, are provided. The information contained herein relates only to the specific product(s). If this product(s) is combined with other materials, all component properties must be considered. Data may be changed from time to time. Be sure to consult the latest edition.					
16.4	Prepared for:	OPI Products, Inc. 13034 Saticoy Street No. Hollywood, CA 91605 USA Tel: +1 (818) 759-2400 Fax: +1 (818) 759-5776 http://www.opi.com	$\mathbf{O} \cdot \mathbf{P} \cdot \mathbf{I}$				
16.5	Prepared by:	ShipMate, Inc. P.O. Box 787 Sisters, Oregon 97759-0787 USA Tel: +1 (310) 370-3600 Fax: +1 (310) 370-5700 http://www.shipmate.com	ShipMate  Dangerous Goods Training & Consulting				

# **SAFETY DATA SHEET**

Page 7 of 7 **SDS-067G** 

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 2001/58 & 1272/2008/EC Standards

SDS Revision Date: 2/8/2016

#### **DEFINITION OF TERMS**

A large number of abbreviations and acronyms appear on a SDS. Some of these that are commonly used include the following:

#### GENERAL INFORMATION:

CAS No. Chemical Abstract Service Number
--

#### **EXPOSURE LIMITS IN AIR:**

ACGIH American Conference on Governmental Industrial Hygienists	
TLV Threshold Limit Value	
OSHA U.S. Occupational Safety and Health Administration	
PEL Permissible Exposure Limit	
IDLH Immediately Dangerous to Life and Health	

#### FIRST AID MEASURES:

CPR	CPR Cardiopulmonary resuscitation - method in which a person whose heart ha					
	stopped receives manual chest compressions and breathing to circulate					
	blood and provide oxygen to the body.					

#### HAZARDOUS MATERIALS IDENTIFICATION SYSTEM: HMIS


#### **HEALTH, FLAMMABILITY & REACTIVITY RATINGS:**

0	Minimal Hazard			
1 Slight Hazard				
2 Moderate Hazard				
3 Severe Hazard				
4	4 Extreme Hazard			



#### PERSONAL PROTECTION RATINGS:

Α			
В			
С		THE SECOND SECON	
D		THE STATE OF THE S	
Е	(E)		
F		THE SECOND	















Clothing & Full Suit

门好 Face Shield & Protective







### OTHER STANDARD ABBREVIATIONS:


NA	Not Available	
NR	No Results	
NE	NE Not Established	
ND Not Determined		
ML	Maximum Limit	
SCBA	SCBA Self-Contained Breathing Apparatus	

#### NATIONAL FIRE PROTECTION ASSOCIATION: NFPA

FLAMMABILI	FLAMMABILITY LIMITS IN AIR:						
Autoignition Temperature	Minimum temperature required to initiate combustion in air with no other source of ignition						
LEL	Lower Explosive Limit - lowest percent of vapor in air, by volume, that will explode or ignite in the presence of an ignition source						
UEL	Upper Explosive Limit - highest percent of vapor in air, by volume, that will explode or ignite in the presence of an ignition source						

#### **HAZARD RATINGS:**

0	Minimal Hazard	
Slight Hazard		
2 Moderate Hazard		
3	Severe Hazard	
4	Extreme Hazard	
ACD	Acidic	
ALK	Alkaline	
COR	Corrosive	
W	Use No Water	
ОХ	Oxidizer	
TREFOIL	Radioactive	
TREFOIL	Radioactive	



#### TOXICOLOGICAL INFORMATION:

LD <sub>50</sub>	Lethal Dose (solids & liquids) which kills 50% of the exposed animals s				
LC <sub>50</sub>	LC <sub>50</sub> Lethal concentration (gases) which kills 50% of the exposed animal				
ppm	Concentration expressed in parts of material per million parts				
TD <sub>Io</sub>	Lowest dose to cause a symptom				
TCLo	Lowest concentration to cause a symptom				
TD <sub>Io</sub> , LD <sub>Io</sub> , & LD <sub>o</sub> or	or Lowest dose (or concentration) to cause lethal or toxic effects				
TC, TC <sub>o</sub> , LC <sub>io</sub> , & LC <sub>o</sub>					
IARC	International Agency for Research on Cancer				
NTP	ITP National Toxicology Program				
RTECS	S Registry of Toxic Effects of Chemical Substances				
BCF	CF Bioconcentration Factor				
TL <sub>m</sub>	Median threshold limit				
log K <sub>ow</sub> or log K <sub>oc</sub>	Coefficient of Oil/Water Distribution				

#### **REGULATORY INFORMATION:**

WHMIS	Canadian Workplace Hazardous Material Information System					
DOT	U.S. Department of Transportation					
TC	Transport Canada					
EPA	EPA U.S. Environmental Protection Agency					
DSL	Canadian Domestic Substance List					
NDSL	. Canadian Non-Domestic Substance List					
PSL	PSL Canadian Priority Substances List					
TSCA	U.S. Toxic Substance Control Act					
EU	EU European Union (European Union Directive 67/548/EEC)					
WGK	Wassergefährdungsklassen (German Water Hazard Class)					

#### WORKPLACE HAZARDOUS MATERIALS IDENTIFICATION (WHMIS) SYSTEM:

0	<b>(*)</b>	<b>(4)</b>	<b>®</b>	$\odot$	(18)		
Class A	Class B	Class C	Class D1	Class D2	Class D3	Class E	Class F
Compress ed	Flammabl e	Oxidizing	Toxic	Irritation	Infectious	Corrosive	Reactive

### EC (67/548/EEC) INFORMATION:

<b>1</b>		M	*		<b>\$</b>	×	×
С	E	F	N	0	Т	Xi	Xn
Corrosive	Explosive	Flammabl e	Harmful	Oxidizing	Toxic	Irritant	Harmful

#### CLP/GHS (1272/2008/EC) PICTOGRAMS:

		<b>®</b>	$\Diamond$			<b>\limits</b>		*
GHS01	GHS02	GHS03	GHS04	GHS05	GHS06	GHS07	GHS08	GHS09
Explosive	Flammable	Oxidizer	Pressurized	Corrosive	Toxic	Harmful Irritating	Health Hazard	Environment