



AMERICAN INTERNATIONAL INDUSTRIES

Rev. No.: 2

SAFETY DATA SHEET

Date: 5-22-2015

Page 1 of 8

IBD UV Top Coat

SECTION 1. IDENTIFICATION

PRODUCT DESCRIPTION

IBD UV TOP COAT

ITEM NUMBER

61214, 97210 (30-1326)

PRODUCT TYPE

Finished Good

RECOMMENDED USE

Nail lacquer

USES ADVISED AGAINST

All other uses


MANUFACTURER

American International Industries
2220 Gaspar Ave
Los Angeles, CA 90040
Phone: (323) 728-2999

EMERGENCY PHONE

CHEM-TEL: 1-(800)-255-3924

SECTION 2. HAZARD IDENTIFICATION

| <i>HAZARD CLASS</i> | <i>CATEGORY</i> | <i>PICTOGRAM</i> |
|--------------------------|--|---|
| Flammable Liquid | Class 2 |  |
| Signal word | Danger | |
| Hazard Statement | Highly Flammable Liquid and Vapor | |
| Hazard Codes | H225 | |
| Precautionary Statements | P102 Keep out of reach of Children P210 Keep away from heat/sparks/open flames/hot surfaces – No Smoking. P233 Keep container tightly closed P 403 + P235 Store in a well ventilated place. Keep cool | |
| Other Hazards | Hazard Symbol: F, Xi | |
| Risk Phrases | R11 Highly Flammable | |



AMERICAN INTERNATIONAL INDUSTRIES

Rev. No.: 2

SAFETY DATA SHEET

Date: 5-22-2015

Page 2 of 8

IBD UV Top Coat

| | |
|----------------|--|
| | R36 Irritating to eyes. R66 Repeated exposure may cause skin dryness or cracking R67 Vapors may cause drowsiness and dizziness |
| Safety Phrases | S16 Keep away from sources of ignition S26 In case of contact with eyes, rinse immediately with plenty of water and see a physician. S33 Take precautionary measures against static discharges |

SECTION 3. COMPOSITION

This product does not contain hazardous chemicals according to the OSHA Hazardous Communication Standard 29 CFR §1910.1200.

| COMPOSITION OF HAZARDOUS CHEMICALS | | |
|------------------------------------|----------|--------------|
| INCI Name | CAS No. | % w/w |
| Butyl Acetate | 123-86-4 | 25.0 -35.0% |
| Ethyl Acetate | 141-78-6 | 30.00-45.00% |
| Isopropyl Alcohol | 67-63-0 | 2.0 – 10.0% |
| | | |

SECTION 4. FIRST AID MEASURES

GENERAL ADVISE

Though this product is non hazardous for its indented use, in all cases, if symptoms persists contact a physician.

ROUTES OF ENTRY

| | |
|--------------|---|
| EYE CONTACT | Immediately flush eyes with water for 15 minutes. Get medical attention, if irritation persists. |
| SKIN CONTACT | Wash skin with water, if irritation persists contact a physician. |
| INHALATION | Remove to fresh air; if breathing continues to be difficult get medical attention immediately. |
| INGESTION | Get medical attention immediately. If swallowed, do NOT induce vomiting. Contact a physician or a poison control center immediately. Never give anything by mouth to an unconscious person. |

MOST IMPORTANT SYMPTOMS/EFFECTS ACUTE OR DELAYED

Non known

**SAFETY DATA SHEET***IBD UV Top Coat**NOTES TO PHYSICIAN*

Treat symptomatically

SECTION 5. FIRE-FIGHTING MEASURES*FLAMMABILITY*

Highly Flammable

FLASH POINT

20°C (68°F)

EXTINGUISHING MEDIA

Dry chemical, carbon dioxide, Halon foam. Water may be ineffective. Water spray may be used to keep fire exposed containers cool and to disperse vapors.

SPECIAL HAZARDS

Vapors can travel to a source of ignition and flashback. "Empty" containers retain product residue (liquid and/or vapor) and can be dangerous. Empty drums should be completely drained, properly bunged and promptly returned to a drum reconditioner, or properly disposed of.

SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS

First responders should wear eye protection. Structural fire-fighters must wear MSHA/NIOSH approved SCBA and full protective equipment. Use a water spray or fog to reduce vapors. Water may not be effective in extinguishing a fire involving this product.

SECTION 6. ACCIDENTAL RELEASE MEASURES*PERSONAL PRECAUTIONS*

Household: Absorb with inert material and place in a appropriate waste disposal
Industrial: Avoid contact with skin, eyes, and clothing. Remove all sources of ignition. Absorb with an inert material and put the spilled material in an appropriate waste disposal. Finish cleaning by spreading water on the contaminated surface and allow to evacuate through the sanitary system

ADVISE FOR EMERGENCY RESPONDERS

Use personal protective equipment.

ENVIRONMENTAL PRECAUTIONS

Household: Do not place spilled product in any drain or water system that can go into the environment.
Industrial: Should not be released into the environment.

METHODS OF SPILL CONTAINMENT AND CLEAN-UP



SAFETY DATA SHEET

IBD UV Top Coat

Highway or railway spills call chemtrec (800) 424-9600 cont. U.S. Collect (202) 483-7616 from Alaska and Hawaii.

Stay upwind and away from spill. Keep all sources of ignition and hot metal surfaces away from spill. Keep out of drains, sewers, or waterways. Use sand or other inert material to dam and contain spill. Do not flush with water; use absorbent pads. For large spills call response team and notify appropriate state/local agencies. Immediately notify the National Response Center (phone number: 800-424-8802) in case if the spill is in excess of EPA reportable quantity.

SECTION 7. HANDLING AND STORAGE

WORK & HYGIENE PRACTICES

Avoid prolonged contact with the product. After use, wash hands and exposed skin with soap and water. Do not eat, drink, or smoke while handling this product.

STORAGE & HANDLING

Keep this material away from heat, sparks, and open flame. Open containers slowly on a stable surface. Keep container closed tightly when not in use. Empty containers may contain residual amounts of the product; therefore handle empty container with care. Store containers in a cool dry place, away from direct sunlight, other light sources, or any intense heat. Store away from incompatible materials as appropriate.

SECTION 8. EXPOSURE CONTROL/ PERSONAL PROTECTION

EXPOSURE GUIDELINES

Household: Exposure guidelines are not relevant when the product is used as directed in a household setting.

Industrial: When working with large quantities of the product, make sure an eye wash station, sink or washbasin is available in the event there is exposure to eyes.

VENTILATION

When working with large quantities of the product, provide adequate ventilation.

RESPIRATORY PROTECTION

No respiratory protection is required under typical circumstances of use and handling. If necessary, use only respiratory protection authorized by U.S. OSHA 29 CFR §1920.134, or applicable U.S. local state regulations,

EYE PROTECTION

Depending on the use of this product splash or safety glasses may be worn in an industrial setting. When necessary refer to U.S. OSHA 29 CFR §1910.133, Canadian standards, or the European standard EN166.

HAND PROTECTION

**SAFETY DATA SHEET***IBD UV Top Coat*

If it is anticipated that prolonged and repeated skin contact will occur during the use of this product, wear neoprene or rubber gloves for routine industrial use. If necessary refer to U.S. OSHA 1910.138, the appropriate standards for Canada or the E.C. member states.

BODY PROTECTION

No special body protection is required for this product under typical use and handling.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

| | |
|---------------------------------|----------------------|
| Appearance | Clear Viscous Liquid |
| Color | Colorless |
| Odor | Solvent |
| pH | Not applicable |
| Viscosity | 250 - 350 |
| Specific Gravity | 0.900 – 0.940 |
| Melting Point/Freezing Point | Not available |
| Boiling Point | Not available |
| Evaporation Rate | Not available |
| Upper/Lower Flammability Limits | Not available |
| Vapor Pressure | Not available |
| Vapor Density | Not available |
| VOC Content | Not available |
| Solubility | Moderate |
| Auto-Ignition Temperature | Not available |

SECTION 10. STABILITY AND REACTIVITY*STABILITY*

Product is stable under ambient conditions when stored properly.

HAZARDOUS DECOMPOSITION

If exposed to extremely high temperatures, the products of decomposition may include irritating vapors and carbon oxide gases (e.g. CO₂, CO).

HAZARDOUS POLYMERIZATION

No data available

CONDITIONS TO AVOID

Do not store over 120°F

INCOMPATIBLE SUBSTANCES



SAFETY DATA SHEET

IBD UV Top Coat

Acids, Alkalis and Peroxides

SECTION 11. TOXICOLOGICAL INFORMATION*TOXICITY DATA*

Toxicity: -LD 50 Rat: - Undefined

Organic solvents in the product may lead to removal of lipid soluble elements of the skin leading to non-allergic dermatitis upon repeated prolonged contact. Vapor from solvents may cause: ill effects to the renal system; central nervous system problems; irritation to the respiratory tracts and other various mucosal membranes.

ACUTE TOXICITY

| | |
|------------------------------|--|
| Principle Routes of Exposure | Absorbed through skin; ingestion. |
| Inhalation | May cause respiratory tract irritation with coughing and shortness of breath. This product has a low vapor pressure and is not expected to present an inhalation hazard at ambient conditions. |
| Skin Contact | This product is not expected to cause any skin irritation upon direct single or repeated and prolonged contact. |
| Ingestion | Ingestion is relatively non-toxic unless aspiration occurs. |
| Eye Contact | May cause mild (minimal) eye irritation. |

CHRONIC TOXICITY

| | |
|------------------------|--------------------------|
| Corrosivity | No information available |
| Sensitization | Non sensitizing |
| Neurological Effects | No information available |
| Reproductive Toxicity | None Known |
| Mutagenic Effects | None Known |
| Developmental Toxicity | None Known |
| Teratogenicity | None Known |
| Carcinogenicity | None Known |

SECTION 12. ECOLOGICAL INFORMATION*ACUTE TOXICITY*

No information available

PERSISTENCE AND DEGRADABILITY

No information available

BIOACCUMULATIVE POTENTIAL

No information available

**SAFETY DATA SHEET***IBD UV Top Coat**BIOACCUMULATIVE POTENTIAL*

No information available

MOBILITY

No information Available

OTHER ADVERSE EFFECTS

No information available

SECTION 13. DISPOSAL CONSIDERATIONS*WASTE DISPOSAL*

Waste disposal must be in accordance with appropriate federal, state, and local regulations

SPECIAL CONSIDERATIONS

None

SECTION 14. TRANSPORT INFORMATION*DOT*

Proper Shipping Name: Paint
Hazard Class: 3, Flammable Liquid
UN ID: UN1263
Packaging Group: II

IATA

Proper Shipping Name: Paint
Hazard Class: 3, Flammable Liquid
UN ID: UN1263
Packaging Group: II

IMDG/IMO

Proper Shipping Name: Paint
Hazard Class: 3, Flammable Liquid
UN ID: UN1263
Packaging Group: II

SECTION 15. REGULATORY INFORMATION*SARA 313*

Toluene >1.0% concentration listed as a "Toxic Chemical"



AMERICAN INTERNATIONAL INDUSTRIES

Rev. No.: 2

SAFETY DATA SHEET

Date: 5-22-2015

Page 8 of 8

IBD UV Top Coat

SARA 311/312 HAZARD CATEGORIES

Reportable Quantities : Toulene (1000 lbs)

CERCLA

Reportable Quantities : Toulene (1000 lbs)

TSCA INVENTORY STATUS

The components of this product are listed on the TSCA Inventory as appropriate

OTHER FEDERAL REQUIREMENTS

This product complies with the appropriate sections of the Food and Drug Administration's 21 CFR subchapter G (Cosmetics).

WHMIS (Canada)

WHMIS Classification: Toluene: B2- Flammable Liquid, D2A - Very toxic material, D2B - Toxic material

STATE REGULATORY INFORMATION

California Proposition 65: Toulene

Warning! This product contains a chemical known to the state of California to cause cancer.

EUROPEAN UNION REQUIREMENTS 67/548/EEC

See section 2 of this document.

SECTION 16. OTHER INFORMATION

DISCLAIMER

This Safety Data Sheet is offered pursuant to OSHA's Hazard Communication Standard, 29 CFR § 1910.1200 and GHS. To the best of A.I.I.'s knowledge, the information contained herein is reliable and accurate as of this date; however, accuracy, suitability or completeness is not guaranteed and no warranties of any type, either expressed or implied, are provided. The information contained herein relates only to the specific product(s). If this product(s) is combined with other materials, all component properties must be considered. Data may be changed from time to time. Be sure to consult the latest edition.