



AMERICAN INTERNATIONAL INDUSTRIES

Safety Data Sheet SuperNail Glue Off

SECTION 1: Identification of the substance/mixture and of the company/undertaking

Product identifier

Product name SuperNail Glue Off

Product number 31500

Relevant identified uses of the substance or mixture and uses advised against

Uses:

Remover

Details of the supplier of the safety data sheet

Name American International Industries
Address 2220 Gaspar Ave
Los Angeles, CA 90040
USA

Telephone 323-728-2999

Emergency telephone number

Chem-Tel: 1(800) 255-3924

SECTION 2: Hazards identification

Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008 (CLP)

- Eye damage/irritation (chapter 3.3), Cat. 2, H319
- Specific target organ toxicity, single exposure (chapter 3.8), Cat. 3, H335,H336
- Flammable liquids (chapter 2.6), Cat. 2, H225
- Skin corrosion/irritation (chapter 3.2), Cat. 2, H315

For the full text corresponding to the "H"-codes displayed in this section, refer to Section 16.

Label elements

Labeling according to Regulation (EC) No 1272/2008 [CLP]

Hazard pictograms

Safety Data Sheet
SuperNail Glue Off



Signal word

Danger

Hazard statement(s)

H319	Causes serious eye irritation
H335	May cause respiratory irritation
H336	May cause drowsiness or dizziness
H225	Highly flammable liquid and vapor
H315	Causes skin irritation

Precautionary statement(s)

P261	Avoid breathing dust/fume/gas/mist/vapours/spray.
P271	Use only outdoors or in a well-ventilated area.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P304+P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do. Continue rinsing.
P312	Call a POISON CENTER/doctor/... if you feel unwell.
P337+P313	If eye irritation persists: Get medical advice/attention.
P403+P233	Store in a well ventilated place. Keep container tightly closed.
P405	Store locked up.
P210	Keep away from heat, hot surfaces, sparks, open flames, and other ignition sources. No smoking.
P233	Keep container tightly closed.
P240	Ground/bond container and receiving equipment.
P241	Use explosion-proof electrical/ventilating/lighting/.../equipment.
P242	Use only non-sparking tools.
P243	Take precautionary measures against static discharge.
P303+P361+P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
P403+P235	Store in a well ventilated place. Keep cool.
P102	Keep out of reach of children

SECTION 3: Composition/information on ingredients

Mixtures

Components

Component	Concentration
ACETONE (CAS no.: 67-64-1; EC no.: 200-662-2; Index no.: 606-001-00-8) CLASSIFICATIONS: Flammable liquids (chapter 2.6), Cat. 2; Eye damage/irritation (chapter 3.3), Cat. 2; Specific target organ toxicity, single exposure (chapter 3.8), Cat. 3. HAZARDS: H225 - Highly flammable liquid and vapor; H319 - Causes serious eye irritation; H336 - May cause drowsiness or dizziness.	90 - 100 %
Butyl Acetate CAS no.: 123-86-4; EC no.: 204-658-1; Index no.: 607-025-00-1) CLASSIFICATIONS: Flammable liquids (chapter 2.6), Cat. 3; Specific target organ toxicity, single exposure (chapter 3.8), Cat. 3. HAZARDS: H226 - Flammable liquid and vapor; H336 - May cause drowsiness or dizziness.	1 - 5 %
Ethyl Acetate (CAS no.: 141-78-6; EC no.: 205-500-4; Index no.: 607-022-00-5) CLASSIFICATIONS: Flammable liquids (chapter 2.6), Cat. 2; Eye damage/irritation (chapter 3.3), Cat. 2; Specific target organ toxicity, single exposure (chapter 3.8), Cat. 3. HAZARDS: H225 - Highly flammable liquid and vapor; H319 - Causes serious eye irritation; H336 - May cause drowsiness or dizziness.	1 - 5 %

SECTION 4: First aid measures

Safety Data Sheet

SuperNail Glue Off

Description of first aid measures

General notes	Though this product is non hazardous for its indented use, in all cases, if symptoms persists contact a physician.
Following inhalation	If breathed in, move person into fresh air. If not breathing, give artificial respiration. Consult a physician.
Following skin contact	Rinse with plenty of water. Get medical attention if irritation develops and persists.
Following eye contact	Rinse thoroughly with plenty of water for at least 15 minutes. Get medical attention if symptoms occur.
Following ingestion	Get medical attention immediately. If swallowed, do NOT induce vomiting. Contact a physician or a poison control center immediately. Never give anything by mouth to an unconscious person.
Self-protection of the first aider	Use personal protective equipment.

Most important symptoms and effects, both acute and delayed

If inhaled for long periods of time, can cause dizziness/drowsiness, headache and nausea.

SECTION 5: Firefighting measures

Extinguishing media

Dry chemical, carbon dioxide, Halon foam. Water may be ineffective. Water spray may be used to keep fire exposed containers cool and to disperse vapors.

Special hazards arising from the substance or mixture

Vapors can travel to a source of ignition and flashback. "Empty" containers retain product residue (liquid and/or vapor) and can be dangerous. Empty drums should be completely drained, properly bunged and promptly returned to a drum reconditioner, or properly disposed of.

Advice for firefighters

First responders should wear eye protection. Structural fire-fighters must wear MSHA/NIOSH approved SCBA and full protective equipment. Use a water spray or fog to reduce vapors. Water may not be effective in extinguishing a fire involving this product.

SECTION 6: Accidental release measures

Personal precautions, protective equipment and emergency procedures

Household: Absorb with inert material and place in a appropriate waste disposal
Industrial: Avoid contact with skin, eyes, and clothing. Remove all sources of ignition. Absorb with an inert material and put the spilled material in an appropriate waste disposal. Finish cleaning by spreading water on the contaminated surface and allow to evacuate through the sanitary system

Environmental precautions

Household: Do not place spilled product in any drain or water system that can go into the environment.
Industrial: Should not be released into the environment.

Methods and material for containment and cleaning up

Highway or railway spills call chemtrec (800) 424-9600 cont. U.S. Collect (202) 483-7616 from Alaska and Hawaii. Stay upwind and away from spill. Keep all sources of ignition and hot metal surfaces away from spill. Keep out of drains, sewers, or waterways. Use sand or other inert material to dam and contain spill. Do not flush with water;

Safety Data Sheet

SuperNail Glue Off

use absorbent pads. For large spills call response team and notify appropriate state/local agencies. Immediately notify the National Response Center (phone number: 800-424-8802) in case if the spill is in excess of EPA reportable quantity.

SECTION 7: Handling and storage

Precautions for safe handling

Avoid prolonged contact with the product. After use, wash hands and exposed skin with soap and water. Do not eat, drink, or smoke while handling this product.

Conditions for safe storage, including any incompatibilities

Keep this material away from heat, sparks, and open flame. Open containers slowly on a stable surface. Keep container closed tightly when not in use. Empty containers may contain residual amounts of the product; therefore handle empty container with care.

Store containers in a cool dry place, away from direct sunlight, other light sources, or any intense heat. Store away from incompatible materials as appropriate.

SECTION 8: Exposure controls/personal protection

Control parameters

CAS: 123-86-4

n-Butyl-acetate

Cal/OSHA: 150 ppm, (ST) 200 ppm PEL inhalation; NIOSH: 150 ppm, (ST) 200 ppm REL inhalation; OSHA: 150 ppm PEL inhalation; 710 mg/m³ PEL inhalation

CAS: 141-78-6

Ethyl acetate

Cal/OSHA: 400 ppm PEL inhalation; NIOSH: 400 ppm REL inhalation; OSHA: 400 ppm PEL inhalation; 1400 mg/m³ PEL inhalation

CAS: 67-64-1

Acetone

Cal/OSHA: 500 ppm, (ST) 750 ppm, (C) 3000 ppm PEL inhalation; NIOSH: 250 ppm REL inhalation; OSHA: 1000 ppm PEL inhalation; 2400 mg/m³ PEL inhalation

Exposure controls

Appropriate engineering controls

Distribution, Workplace and Household Settings: Ensure adequate ventilation. Product Manufacturing Plant (needed at Product-Producing Plant ONLY): Where reasonably practicable this should be achieved by the use of local exhaust ventilation and good general extraction.

Personal protection equipment

Eye and face protection

Depending on the use of this product splash or safety glasses may be worn in an industrial setting. When necessary refer to U.S. OSHA 29 CFR §1910.133, Canadian standards, or the European standard EN166.

Skin protection

Skin Protection: None required with normal household use. Industrial Setting: Protective gloves (for hands) and protective clothing are required where repeated or prolonged skin contact may occur.

Body protection

No special body protection is required for this product under typical use and handling.

Safety Data Sheet

SuperNail Glue Off

Respiratory protection

No respiratory protection is required under typical circumstances of use and handling. If necessary, use only respiratory protection authorized by U.S. OSHA 29 CFR §1920.134, or applicable U.S. local state regulations,

SECTION 9: Physical and chemical properties

Information on basic physical and chemical properties

Appearance	Transparent liquid
Odour	Fragrant myrrh
Odour threshold	No data available.
pH	No data available.
Melting point / freezing point	No data available.
Initial boiling point and boiling range	No data available.
Flash point	19 C (67 F)
Evaporation rate	No data available.
Flammability (solid, gas)	Flammable
Upper/lower flammability limits	No data available.
Vapour pressure	No data available.
Vapour density	No data available.
Relative density	No data available.
Solubilit(ies)	Miscible
Partition coefficient: n-octanol/water	No data available.
Auto-ignition temperature	No data available.
Decomposition temperature	No data available.
Viscosity	No data available.
Explosive properties	No data available.
Oxidising properties	No data available.

SECTION 10: Stability and reactivity

Reactivity

No data available

Chemical stability

Stable under recommended storage conditions.

Incompatible materials

Acids, Alkalies, and Peroxides

Hazardous decomposition products

If exposed to extremely high temperatures, the products of decomposition may include irritating vapors and carbon oxide gases (e.g. CO₂, CO).

SECTION 11: Toxicological information

Information on toxicological effects

Acute toxicity

Vapors may cause drowsiness and dizziness.

Oral:

Low toxicity: LD₅₀>2000 mg/kg, Rat Aspiration into the lungs when swallowed or vomited may cause chemical pneumonitis which can be fatal.

Safety Data Sheet

SuperNail Glue Off

Dermal:

Low toxicity: LD50>2000 mg/kg, Rabbit

Skin corrosion/irritation

Causes skin irritation and exposure to the skin can cause dermatitis.

Serious eye damage/irritation

May be irritating to eyes

Germ cell mutagenicity

No data available.

Carcinogenicity

No data available.

Reproductive toxicity

No data available.

STOT-single exposure

May cause respiratory irritation

STOT-repeated exposure

No data available.

Aspiration hazard

No data available.

SECTION 12: Ecological information

Toxicity

Do not let product enter drains.

Persistence and degradability

No data available.

Bioaccumulative potential

No data available.

Mobility in soil

No data available.

SECTION 13: Disposal considerations

Waste treatment methods

Disposal of the product

Dispose of in accordance with federal, state and local regulations.

SECTION 14: Transport information

DOT (US)

UN Number: 1993

Class: 3

Packing Group: II

Proper Shipping Name: Flammable liquid, n.o.s. (Acetone, Ethyl acetate, Butyl acetate)

Safety Data Sheet

SuperNail Glue Off

IMDG

UN Number: 1993

Class: 3

Packing Group: II

Proper Shipping Name: Flammable liquid, n.o.s. (Acetone, Ethyl acetate, Butyl acetate)

IATA

UN Number: 1993

Class: 3

Packing Group: II

Proper Shipping Name: Flammable liquid, n.o.s. (Acetone, Ethyl acetate, Butyl acetate)

SECTION 15: Regulatory information

Safety, health and environmental regulations/legislation specific for the substance or mixture

Massachusetts Right To Know Components

Chemical name: Butyl acetate

CAS number: 123-86-4

New Jersey Right To Know Components

Common name: n-BUTYL ACETATE

CAS number: 123-86-4

Pennsylvania Right To Know Components

Chemical name: Acetic acid, butyl ester

CAS number: 123-86-4

Massachusetts Right To Know Components

Chemical name: Ethyl acetate

CAS number: 141-78-6

New Jersey Right To Know Components

Common name: ETHYL ACETATE

CAS number: 141-78-6

Pennsylvania Right To Know Components

Chemical name: Acetic acid ethyl ester

CAS number: 141-78-6

Massachusetts Right To Know Components

Chemical name: Acetone

CAS number: 67-64-1

New Jersey Right To Know Components

Common name: ACETONE

CAS number: 67-64-1

Pennsylvania Right To Know Components

Chemical name: 2-Propanone

CAS number: 67-64-1

SECTION 16: Other information

Full text of hazard statements referenced in Section 2

Safety Data Sheet SuperNail Glue Off

H225	Highly flammable liquid and vapor
H319	Causes serious eye irritation
H335	May cause respiratory irritation
H336	May cause drowsiness or dizziness
H315	Causes skin irritation
H225	Highly flammable liquid and vapor

Further information/disclaimer

This Safety Data Sheet is offered pursuant to OSHA's Hazard Communication Standard, 29 CFR § 1910.1200 and GHS. To the best of A.I.I.'s knowledge, the information contained herein is reliable and accurate as of this date; however, accuracy, suitability or completeness is not guaranteed and no warranties of any type, either expressed or implied, are provided. The information contained herein relates only to the specific product(s). If this product(s) is combined with other materials, all component properties must be considered. Data may be changed from time to time. Be sure to consult the latest edition.